











Dimmer Compatibility Guide

Specialty: LED Mini: G9 Product Family Name: Item Number: 770591 Ordering Code: LED4G9/27K/120/F/D

					Lamps p	er Dimmer	
					Recommended		
	Manufacturer	Product	Model Number	Overall Rating	Minimum	Maximum Tested*	Notes
		IllumaTech	IPI06	Good	1	6	Flicker at LE with 1, dims down to 15% with 1-6
	Leviton	SureSlide	6633-P	Good	1	6	Flicker at LE with 1, dims down to 5% with 1-6
		Vizia	VPI06-1LZ	Good	2	6	Dims down to 5% with 2-6
		Toggler	TG-600	Good	1	6	Dims down to 15% with 1-6
Incandescent/Halogen (Triac/Phase	Lutron	Diva	DV-600	Good	1	6	Flicker at LE with 1, dims down to 5% with 1-6
Cut/Leading Edge Dimmers)	Lucion	Skylark	S-600	Best	1	6	Dims down to 5% with 1-6
		Maestro	MAW-600	Bad	4	6	Dims down to 5% with 4-6
		Titan	CD703-PW	Good	1	6	Flicker at LE with 3, dims down to 10% with 1-6
	Legrand	Harmony	D703-PTC	Good	1	6	Flicker at Med with 1-3, flicker at HE with 1, dims down to 1% with 1-6
		Harmony	H703-PTC	Good	1	6	Flicker at HE and Med with 1, dims down to 5% with 1-6
		IllumaTech	IPL06	Good	1	6	Flicker at LE, dims down to 1% with 1-6
Cut/Leading Edge Dimmers) CFL/LED Electronic Low Voltage Magentic Low Voltage	Leviton	Sureslide	6674	Best	1	6	Dims down to 5% with 1-6
		Decora	6672	Best	1	6	Dims down to 5% with 1-6
		Skylark	CTCL-153	Best	1	6	Adjust dial at 5% with 1-6
		Diva	DVCL-153PL	Best	1	6	Adjust dial at 5% with 1-6
CEL/LED	Lutron	Maestro	MACL-153MLH	Best	1	6	Adjust dial at 5% with 1-6
Citytes	Lucion	Skylark	SCL-153P	Best	1	6	Adjust dial at 5% with 1-6
		Toggler	TGCL-153PH	Best	1	6	Adjust dial at 5% with 1-6
		Radio RA	RA2RR-6CL-PD	Best	1	6	Adjust dial at 5% with 1-6
		Harmony	DCL453-PTC	Best	1	6	Dims down to 5% with 1-6
	Legrand	Harmony	HCL453PTC	Best	1	6	Dims down to 5% with 1-6
		Adorne Paddle	ADPD453LM2	Best	1	6	Dims down to 15% with 1-6
		Vizia VPE04 Good 1 6 Dims down to 5% with 1-6	Dims down to 5% with 1-6				
	Leviton	IllumaTech	IPE04	Good	1	6	Flicker at LE with 1-6, dims down to 5% with 1-6
		Decora	6615-P	Good	1	6	Dims down to 25% with 1-8
		Skylark Countour	CTELV-303P	Good	1	6	Flicker at LE with 1-6, dims down to 5% with 1-6
Electronic Low Voltage		Diva	DVELV-300P	Good	1	6	Dims down to 5% with 1-6
	Lutron	Maestro	MAELV-600	Good	1	6	Dims down to 5% with 1-6
		Skylark	SELVB-300P	Good	1	6	Dims down to 5% with 1-6
		VIERTI	VTEL-600M-W	Best	1	6	Dims down to 6% with 1-6
	Legrand	Scene Director	SCELV	Good	1	6	Dims down to 15% with 1-6
				<u> </u>			
	Leviton	Vizia	VPM-06	Good	2	6	Dims down to 5% with 1-6
Magentic Low Voltage		Decora	6613-P	Best	1	6	Dims down to 5% with 1-6
	Lutron	Maestro	MALV-600	Bad	4	6	Flicker at LE with 4-6, dims down to 5% with 4-6
	Legrand	Harmony	DLV703-PW	Best	1	6	Dims down to 5% with 1-6
		Titan	CDLV703-PW	Best	1	6	Dims down to 10% with 1-6
		Adorne SofTap	ADTP703TU	Best	1	6	Dims down to 10% with 1-6
	Legrand	Miro Decorator	DRD4-W	Bad	1	6	Flicker at LE with 4-6, dims down to 5% with 1-6
		Harmony	H703PTUTC	Best	1	6	Dims down to 15% with 1-6
Universal		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims down to 3% with 1-6
		Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 5% with 1-6
	Cooper	Decorator	DAL06P-C2-K-L	Bad	1	6	Flicker at LE with 1-6, dims down to 5% with 1-6
		Skye	SAL06P-W-K-L	Bad	1	6	Flicker at LE with 1-6, dims down to 1% with 1-6

Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer *May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
Low End (L.E.) Dead Travel	Determines now much, if any, dead daver exists at the top and bottom of the diffinite strange. Dead daver is when the shader can be moved without anecting the light level.

Contact Information: Bulbrite Industries Inc. 145 West Commercial Avenue Moonachie, New Jersey 07074 PHONE: 1-800-528-5555 FAX: 1-800-441-7708 Email: Productsupport@bulbrite.com ©2017 Subcrite Industries Inc.













roduct Family Name:	Specialty: LED Mini: G9
em Number:	770591
Ordering Code:	LED4G9/27K/120/F/D

					Lamps pe	r Dimmer	
	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	Decora	RTD01 (fan & dimmer)	Good	1	6	Dims down to 5%, Drop out at LE
	Lutron	Ariadni	AY2-LFSQ (fan & dimmei	Good	1	6	Dims down to 5%,
		Diva	DVFSQ-LFH (fan & switcl	Good	1	6	This fan control only has a on/off switch without dimming function, no flicker
		Skylark	SFSQ-LFH (fan & switch)	Good	1	6	This fan control only has a on/off switch without dimming function, no flicker
		Skylark	S2-LFSQ (fan & dimmer)	Good	1	6	Dims down to 6%
	Legrand	De-Hummer	LSDC16WV (fan & dimm	Good	1	6	Dims down to 5%
	•		•	•			
C.L Dimmer	Lutron	Maestro	MACL-LFQ (fan & dimme	Best	1	6	Dims own to 7%

Dimmer Compatibility Guide For Fan Speed Control/Dimmer

One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth. One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These Most of the following observed: No flickering and some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These Most of the following observed: No flickering at some point may exist. Dead travel level. These Performance of the following observed: No flickering at some point may exist. Dead travel level. These	Bad One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth. Good One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting Best Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.	
One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output. Petermines how much if any dead travel exists at the top and hottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting est Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output. Betermines how much if any dead travel exists at the ton and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.	
Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output. End (H.E.) Dead Travel Determines how much if any dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output. gh End (H.E.) Dead Travel Determines how much if any dead travel exists at the ton and hottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.	
End (H.E.) Dead Travel Determines how much if any dead travel exists at the ton and hottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level	gh End (H.E.) Dead Travel Determines how much if any dead travel exists at the ton and hottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level	he light level. These
Determines now much, if any, dead daver exists at the top and bottom of the diminer strange. Dead daver is when the shall be moved without affecting the light level.	we End (L.E.) Dead Travel	
end (E.E.) Dead Travel		