



Item#: **55643** LED 96" TANDEM STRIP FIXTURE LED READY FIXTURE

# **FEATURES**

- Use 30% less energy than a traditional fluorescent fixture
- · Die formed, and rigidly fabricated
- LED ready with non-shunted sockets
- Pre-wired at both ends
- Works with both Single-End and Double-End Direct
  Wire lamps
- Designed for surface or chain mounting

## **APPLICATION**

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL	

Lamp Type (not included)	Т8
Number of Lamps	4
Voltage	120-277V
ENVIRONMENT	
Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
ngress Protection Rating	IP40
LIFESPAN	
Warranty (Years)	2

## CONSTRUCTION

Housing	22 Gauge C.R.S	
Base / Power Supply	Hard Wired	
Finish	High Gloss Baked White Enamel	

## QUALIFICATIONS



Operating temperature may vary depending on the lamps used. • Specifications are subject to change without notice.

# Item#: **55643** LED 96" TANDEM STRIP FIXTURE



#### **DIMENSIONS** (Inches)

Length	96"
Width	4.4"
Height	2.1″
Weight (Lbs)	

<b>SUPPORTING DOCUMENTS</b> (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768020670	97.6" x 4.7" x 2.3"	8.8
Country of Origin	China			
HS Tariff	9405.10.6020			

### ORDERING

ITEM#	DESCRIPTION	CASE
55643	LED 8FT TANDEM STRIP FIXTURE FOR 4 T8	1
ACCESSOR	IES	
54896	LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30FT DIA, 8-40FT HEIGHT 800W/1200W • 120/277V	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898	100
45005	WIRE GUARD FOR 4FT 2L STRIP FIXTURE/WHITE	1
55004	(1) WHITE REFLECTOR FOR 4FT OR 8FT STRIP FIXTURE	1
REPLACEM	IENT PARTS	
556437	SOCKET AND WIRE SET ONLY FOR LED 8FT STRIP FIXTURE FOR 4 T8/DE	1

## **ADDITIONAL INFORMATION:**

• Pairs with Direct Wire Single-End or Double-End UL Type B Lamps. Follow specific lamp installation wiring instructions for correct wiring.