



**S11951** - 7 Watt; 18 Inch; T8 Linear LED; Medium Bi-Pin G13Base; 4000K; 50000 Average Rated Hours; 750 Lumens; Type B Ballast Bypass


**GENERAL**

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	18.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
Total Harmonic Distortion	25%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.058-0.025A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	18.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	15W
Incandescent Equivalent	75W

**ELECTRICAL**

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-13F to +104F (-25C to +40C)
Lumens	750L
Volts	120V-277V
Watts	7W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.1
MOL	17.8

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923119514
Case Cube	0.626
Case Height	7.3
Case Length	20.3
Case Quantity	25
Case UPC	10045923119511
Case Weight	8.0
Case Width	7.3
EA Cube	0.0126
EA Height	1.1
EA Length	18.0
EA Quantity	1
EA Weight	0.23
EA Width	1.1
Pack Type	Sleeve
Web Length	17.8
Web Width	1.1

**COMPLIANCE**

FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	ETL Sanitation listed (conforms to NSF)
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified, ETLus - Sanitation Recognized Component
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No