

Level 2 EVSE Charging Stations

FEATURES

PRODUCT FEATURES

Modern compact design with robust construction for maximum durability

- Up to 8X Faster than Level 1
- SAE J1772
- 208-240VAC Single Phase 40A Supply Circuit
- 7.2 – 7.7 kW
- Modern Compact Design and Durability
- Indoor and Outdoor Use – NEMA 4 rated
- Multiple Cord Length Options
- Adjustable Maximum Current Output: 32A, 30A, 24A, 16A (to support multiple circuit ratings 40A, 30A, 20A)
- Single and Dual Station Options
- Hardwire or Inlet Adapter – NEMA 6-50 Plug
- Wall or Pedestal Mount



EVSE



iEVSE®



iEVSE Plus

Product Selections	Features	EVSE	iEVSE®	iEVSE Plus
Non-Networked	Standard Model— No Network Capability	✓		
Wi-Fi Enabled	<ul style="list-style-type: none"> ▪ Access Control ▪ Control Data Collection ▪ Demand Response 		✓	✓
Wi-Fi & LTE Cellular	<ul style="list-style-type: none"> ▪ Local Load Management ▪ Mobile App Capability ▪ Remote Monitoring 			✓
RFID Technology	Supports RFID Card Access Control & User Authorization			✓

Cable Management Options



Cable Retractor



EvoReel® with Charge Cable



Dual Port 6 ft. Pedestal with EvoReel®



Single Port 4 ft. Pedestal

