

LED Luminaires

Mini Bullet Flood Series

- Toolless adjustable head for precise illumination
- Reliable high lumen output and efficient COB LED
- Adjustable visor
- Multiple color temperatures
- Quick and easy installation
- Multiple finishes

Specifications

Description

The Mini Bullet Flood provides premium performance for increased safety and security. Featuring an efficient 10W LED floodlight supplying full light protection. With a sleek modern design and robust weather proof construction, the Mini Bullet is ideal for outdoor applications.

Performance

- Color temperatures: 3000K, 5000K
- Lifetime: more than 30,000 hrs
- >1050 Lumens
- >105 lm/W
- >80 CRI
- 120-277V
- Operating temperature: -40°C to 60°C

Certifications

- ETL
- Wet location



Construction

- Die-cast aluminum housing for superior thermal performance
- Internally sealed design to shield water and dust from entry
- Transparent PC optics
- Black and bronze finish

Mini Bullet Flood Series

Ordering Logic

| Series | - | Wattage | - | CCT | - | Voltage | - | Finish |
|--------------------|---|----------|---|--------------------------|---|----------------|---|---------------------------|
| MBUL = Mini Bullet | | 10 = 10W | | 30 = 3000K 50 = 5000K | | U = 120-277VAC | | BL = Black BZ = Bronze |

Ordering Information

| Product SKU | Product Code | Product Description |
|--------------------|-----------------|---|
| 24950 | MBUL-10-30-U-BZ | Mini Bullet Flood, 10 Watt, 3000K, Universal 120-277 VAC, Bronze Finish |
| 24951 | MBUL-10-30-U-BL | Mini Bullet Flood, 10 Watt, 3000K, Universal 120-277 VAC, Black Finish |
| 24952 | MBUL-10-50-U-BZ | Mini Bullet Flood, 10 Watt, 5000K, Universal 120-277 VAC, Bronze Finish |
| 24953 | MBUL-10-50-U-BL | Mini Bullet Flood, 10 Watt, 5000K, Universal 120-277 VAC, Black Finish |
| Accessories | | |
| 998100 | GS08 | 8" GROUND STAKE PVC 1629 |

Performance Table

| Model Number | Nominal Wattage | 3000K | | 5000K | |
|-----------------|-----------------|--------|----------------|--------|----------------|
| | | Lumens | Efficacy (LPW) | Lumens | Efficacy (LPW) |
| MBUL-10-XX-X-XX | 10W | 1239 | 129 | 1284 | 136 |

Mini Bullet Flood Series

Specifications Table

| | MBUL-10-30-U-XX |
|-----------------------|------------------------------|
| Nominal Wattage | 10W |
| Lumens | 1239-1284 |
| CCT | 3000K, 5000K |
| Efficacy | 128 - 136 LPW |
| Amperage | 120VAC(0.083A) 277VAC(.036A) |
| Beam Angle | 100° |
| CRI | 80 CRI |
| L70 Lifetime (Hrs) | 30,000 |
| Voltage | 120-277V |
| Power Factor | >0.9 |
| Housing | Die-Cast Aluminum Housing |
| Lens | PC Optics |
| Operating Temperature | -40°C to 60°C |
| Listings | ETL |
| Environment | Wet Location |
| Weight | 0.55 lbs |
| Warranty | 5 Years Standard |

Dimensions

