

# **LED LINEAR FIXTURE**

## SUSPENDED UP & DOWN LIGHT

### Model No. EUD4-50W103sw-W

This 50-Watt, 4-foot up and down light is a CCT selectable suspension light that is perfect for commercial spaces such as: office buildings, and healthcare facilities where quality light is needed. This light gives a long life of quality and equal light distribution in a variety of commercial spaces, and it offers convenience by allowing you to choose between Soft White (3000K), Bright White (4000K), and Cool White (5000K) all in one unit. Other notable features include: 0-10V dimming, 50,000 hours of life, and operates on a 120-277V line. Accessories Includes

















50Watts





Dual CCT Tunable



Dimmable





Easy and fast installation

#### **Electrical Specifications**

|            | Lumen Output | Input Power | Input Voltage | Luminous Efficacy | ССТ                    | Estimated Yearly Cost |
|------------|--------------|-------------|---------------|-------------------|------------------------|-----------------------|
| Total      | 6500 lm      | 50 W        | AC120-277V    | 130 lm/W          | 3000K / 4000K<br>5000K | \$ 6.02               |
| Up Light   | 1950 lm      |             |               |                   |                        |                       |
| Down Light | 4550 lm      |             |               |                   |                        |                       |


| Beam Angle | Center Beam | CRI | Power Factor | Input Current | Base | Lamp Lifespan |
|------------|-------------|-----|--------------|---------------|------|---------------|
| 100°       | 60          | 80  | 0.9          | 0.43 A        | N/A  | 50,000 Hrs.   |


#### **Mechanical Specifications**

| Rating     | Operational Temperature | Inner Box QTY. | Master Box QTY. | Dimensions(in.)  | UPC Code     |
|------------|-------------------------|----------------|-----------------|--|--------------|
| Damp Rated | 10°F - 170°F            | 1 pc           | 4 pcs           | 47.48"(W) x 2.75"(H) x 3.15"(D)<br>78.74"(Wire Connecor) | 811174034810 |

#### **Product Dimensions**

#### **Photometric Data**





#### \*Independant Up & Down **CCT Tunable Switches**

