

TCP's LED Recessed Flat Face Snap-In CCT Selectable Downlights are the perfect choice for remodeling or new construction projects. The slim, energy-efficient design is easy to install and offers a rated lifetime of 50,000 hours.

## Reasons to choose the LED Recessed Flat Face Snap-In CCT Selectable Downlights from TCP

- 4", 6", and 8" diameter sizes
- Direct wire no recessed can required
- Integrated junction box on 4" and 6" models
- Easy installation
- Dimmable
- Slim, low-profile design

- Excellent color consistency
- Selectable CCT (27K/30K/35K) or (30K/40K/50K)
- 50,000 hour rated life
- UL approved for damp locations
- IC rated
- Back-lit technology

### Ideal Applications

- Retrofits
- New construction
- Residential
- Office

- Retail
- Hospitality
- Drop ceilings
- Remodeling









# LED Recessed Flat Face Snap-In CCT Selectable Downlights

### **Applications**

Ideal for dimmable 4", 6" and 8" retrofit or new construction downlight applications.

#### Construction

- Integrated junction box for direct wire application (4" and 6" models)
- 8" models have external junction box
- Spring loaded tabs for easy installation

#### Electrical

- UL approved for damp locations
- Easily access wiring for quick installation
- 50,000 hour rated life

### **Optics**

- Excellent color consistency
- Smooth, uniform dimming (only with 120V application)
- Highly efficient LEDs and driver
- Triac dimming



#### Accessories

• 4"/6" Adjustable Frame Kit is also available: 46INFRAMEKIT











# LED Recessed Flat Face Snap-In CCT Selectable Downlights

LED Recessed Flat Face Snap-In CCT Selectable Downlights										
ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	LUMENS	LPW	CCT SELECTABLE	BEAM ANGLE	MOL (IN)	DIAMETER (IN)
DR4BLCCT1	4" SNAPIN CCT 27/30/35	120	75	10	850	85	27K/30K/35K	90°	3	5
DR4BLCCT2	4" SNAP-IN CCT 30/40/50	120	75	10	850	85	30K/40K/50K	90°	3	5
DR6BLCCT1	6" SNAP-IN CCT 27/30/35	120	85	14	1100	78.6	27K/30K/35K	100°	3	7.125
DR6BLCCT2	6" SNAP-IN CCT 30/40/50	120	85	14	1100	78.6	30K/40K/50K	100°	3	7.125
DR8CCT1	8" SNAP-IN CCT 27/30/35	120	120	18	1400	77.8	27K/30K/35K	110°	1.5	8.75
DR8CCT2	8" SNAP-IN CCT 30/40/50	120	120	18	1400	77.8	30K/40K/50K	110°	1.5	8.75









## LED Recessed Flat Face Snap-In CCT Selectable Downlights

TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

BRAND	MODEL
LUTRON	AYCL-153P
	CTCL-153PD-H
	CTCL-53PD-H
	DV-600P
	DV-600PR-VVH
	DV-603PH-WH
	DVCl-153P
	LGCL-153P
	MACL_153M
	MSCL-OP153M
	PD-6WCL
	SCI-153PR
	SELV-300P
	TGCL-153P
	MRF2S-6ELV12O-WH
LEVITON	6811
	6602
	6631
	6672
	6672·L
	6674
	DSL06
	IPLO6
COOPER	DALO6P
	SALO6P

<sup>\*</sup>Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an onsite test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.





