

LIGHTING CONTROLS

COMPATIBILITY GUIDE

WITH CONTROLS READY LUMINAIRES




INDOOR							
	CN-REMOTE	CN-RTMST Microwave	CN-RTPSW PIR*	CEA-RDW	CN-RDMSW** PIR*	CNA-RDMSW PIR*	CN-MGMST
 FlatMax Flat Panels & Flat Panel Retrofit							
 ArcMax Troffer & Troffer Retrofit							
 LS Strip & RS Strip							
 LSV Vapor Tight							
 LSU Utility Wrap							
 ECO High Bay							
 Linear High Bay							
 Round High Bay							
 Magnetic Retrofit Bar Kit							

Remote control needed for commissioning, except when using Photocell only nodes.

*PIR requires line of sight and cannot not be used in products behind the lens

**To use CN-RDMSW with the above linear and highbay products, the CEA-RDW External adapter also needs to be purchased separately

c-Max Basic Controls Compatibility Guide

OUTDOOR					
	CN-REMOTE	CN-RTMST Microwave	CN-RTPCT Photocell	CN-RDMSB PIR*	CN-RDPCB Photocell
 Open Face Wall Pack					
 Cutoff Wall Pack					
 Canopy					
 Barn Light					
 M Series					
 AE Slim Area Light					
 Path					

Remote control needed for commissioning, except when using Photocell only nodes.

*PIR requires line of sight and cannot not be used in products behind the lens

INDOOR								
	NN-RTPSW	NN-RTW	CEA-RDW	NN-RDMSW**	NN-RDW	NNA-RDMSW	NNA-RDW	NN-MGT
 FlatMax Flat Panels & Flat Panel Retrofit								
 ArcMax Troffer & Troffer Retrofit								
 LS Strip & RS Strip								
 LSV Vapor Tight								
 LSU Utility Wrap								
 ECO High Bay								
 Linear High Bay								
 Round High Bay								
 Magnetic Retrofit Bar Kit								
 12V RCF DownLights								

MaxLite c-Max Network controls portfolio includes many other devices such as powerpacks and wall switches that are not shown in this compatibility chart. For more details, refer to the product brochure.



All indoor network sensors are compatible with the c-Max mobile App and wall switches (WNS1-W, WNS3-W, WNS5-W, WNS8-W, WNS3U-W & WNS7U-W).



*PIR requires line of sight and cannot not be used in products behind the lens.

**To use NN-RDMSW with the above linear and highbay products, the CEA-RDW External adapter also needs to be purchased separately.

OUTDOOR



NN-RTW

CEA-RDB**

NN-RDMPBXR

NN-RDB




Open Face Wall Pack



Cutoff Wall Pack



Thin Cutoff Wall Pack



Canopy



Barn Light



M Series



AE Slim Area Light



PathMax Slim Bollards



MaxLite c-Max Network controls portfolio includes many other devices such as powerpacks and wall switches that are not shown in this compatibility chart. For more details, refer to the product brochure.

*PIR requires line of sight and cannot not be used in products behind the lens.

Round nodes (NN-RD*) can be used with the CEA-RDB External Adapter.



All outdoor network sensors are compatible with the c-Max mobile App.

INDOOR					
	NN-RTW-SL	NN-RTPSW-SL PIR*	CEA-RDW	NN-RDMSW-SL** PIR*	NN-RDW-SL PIR*
 FlatMax Flat Panels & Flat Panel Retrofit					
 ArcMax Troffer & Troffer Retrofit					
 LS Strip & RS Retrofit Strip					
 LSV Vapor Tight					
 LSU Utility Wrap					
 ECO High Bay					
 Linear High Bay					

MaxLite c-Max Network Partner - Silvair portfolio includes many other devices such as powerpacks and wall switches that are not shown in this compatibility chart. For more details, refer to the product brochure.

Remote control needed for commissioning, except when using Photocell only nodes.

*PIR requires line of sight and cannot not be used in products behind the lens

**To use CN-RDMSW with the above linear and highbay products, the CEA-RDW External adapter also needs to be purchased separately