



# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX


## LED CENTER BASKET FIXTURE

**DESCRIPTION**

LED Center Basket Fixtures | 120 – 277V Input | Frosted Lens | 0 –10V Dimming

**APPLICATION**

Used for commercial recessed ceiling applications



**10 YEAR LIMITED WARRANTY**

**PRODUCT FEATURES**

- Features Keystone Color Select technology. Adjust CCT between 3500/4000/5000K
- Features Keystone Power Select technology. (see Performance Specifications for details)
- Powered by Keystone 0 –10V dimming LED drivers with 12V Aux
- Architectural grade center basket volumetric design
- LED lifetime: L70 >100,000 hours @ 25°C fixture ambient
- Ambient operating temperature: -20°C/-4°F to 40°C/104°F
- Compatible with Keystone SmartSafe emergency backups
- Low optical flicker
- THD: < 20%
- Power factor > 0.95
- IC Rated
- Meets FCC Part 15, Class B
- LED chip lifetime: L70 >100,000 hours @ 25°C/77°F ambient fixture temperature


**PERFORMANCE SPECIFICATIONS OVERVIEW**

Catalog Number	Size	Input Voltage	Wattage	CCT	Lumen Output	Efficacy	CRI	Lifetime
KT-CBLE35PS-14C-8CSA-VDIM /CR	1x4	120–277V	24/30/35W	3500K /4000K /5000K	3120/3900/4550lm	130 lm/W	> 80	50,000 hrs
KT-CBLE24PS-22C-8CSA-VDIM /CR	2x2		15/18/24W		1950/2340/3120lm			
KT-CBLE35PS-22C-8CSA-VDIM /CR	2x2		24/30/35W		3120/3900/4550lm			
KT-CBLE30PS-24C-8CSA-VDIM /CR	2x4		20/25/30W		2600/3250/3900lm			
KT-CBLE45PS-24C-8CSA-VDIM /CR	2x4		30/38/45W		3900/4940/5850lm			

\* Preset to highest lumen output  
 \* Color Uniformity: CCT (Correlated Color Temperature) range as per guidelines outlined in ANSI C78.377-2017

**CONTROLS READY**

Features a Control Ready design that allows the installation of multitude of sensor options, including Keystone’s Smart loop System. See chart below for possible sensor solutions and page 11 for all Ordering Options.




/CR Endcap- Features a Controls ready solution that can be used with or without KTSL-FC5-12V-IM-PIR Sensor



/FC5 Endcap- Features a preinstalled KTSL-FC5-PIR-IM Smartloop Sensor for quick and easy installation on the jobsite



Custom Sensor Solution Endcap - please contact keystone for more information... lead times and MOQ may apply




# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE

**PRODUCT SPECIFICATIONS DETAILED**

Catalog Number	Size	Input Voltage	Wattage	CCT	Lumen Output	Efficacy
KT-CBLE35PS-14C-8CSA-VDIM /CR	1x4	120-277V	24W	3500K	3240	130lm/W
				4000K	3312	134lm/W
				5000K	3336	135lm/W
			30W	3500K	3900	128lm/W
				4000K	4050	132lm/W
				5000K	4080	133lm/W
			35W	3500K	4375	125lm/W
				4000K	4515	129lm/W
				5000K	4550	130lm/W
KT-CBLE24PS-22C-8CSA-VDIM /CR	2x2	120-277V	15W	3500K	2025	130lm/W
				4000K	2070	134lm/W
				5000K	2085	135lm/W
			18W	3500K	2340	128lm/W
				4000K	2430	132lm/W
				5000K	2448	133lm/W
			24W	3500K	3000	125lm/W
				4000K	3096	129lm/W
				5000K	3120	130lm/W
KT-CBLE35PS-22C-8CSA-VDIM /CR	2x2	120-277V	24W	3500K	3240	130lm/W
				4000K	3312	134lm/W
				5000K	3336	135lm/W
			30W	3500K	3900	128lm/W
				4000K	4050	132lm/W
				5000K	4080	133lm/W
			35W	3500K	4375	125lm/W
				4000K	4515	129lm/W
				5000K	4550	130lm/W
KT-CBLE30PS-24C-8CSA-VDIM /CR	2x4	120-277V	20W	3500K	2700	130lm/W
				4000K	2760	134lm/W
				5000K	2780	135lm/W
			25W	3500K	3250	128lm/W
				4000K	3375	132lm/W
				5000K	3400	133lm/W
			30W	3500K	3750	125lm/W
				4000K	3870	129lm/W
				5000K	3900	130lm/W



# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE


### PRODUCT SPECIFICATIONS DETAILED (CONTINUED)

KT-CBLED45PS-24C-8CSA-VDIM /CR	2x4	120-277V	30W	3500K	4050	130lm/W
				4000K	4140	134lm/W
				5000K	4170	135lm/W
			38W	3500K	4940	128lm/W
				4000K	5130	132lm/W
				5000K	5168	133lm/W
			45W	3500K	5625	125lm/W
				4000K	5805	129lm/W
				5000K	5850	130lm/W


### PHOTOMETRIC SPECIFICATIONS

KT-CBLED35PS-14C-8CSA-VDIM /CR

#### ISOCANDELA PLOT




#### POLAR CANDELA DISTRIBUTION




#### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30	1,175.7	26.9%
0-40	1,908.3	43.7%
0-60	3,364.1	77.1%
60-90	994.9	22.8%
70-100	430.1	9.9%
90-120	1.3	0%
0-90	4,359.0	99.9%
90-180	4.4	0.1%
0-180	4,363.3	100%

#### FLUX CHART



Height ■ Vertical Spread: 102.8°  
 ■ Horizontal Spread: 120.0°




# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE


### PHOTOMETRIC SPECIFICATIONS (CONTINUED)

KT-CBLED24PS-22C-8CSA-VDIM /CR

#### ISOCANDELA PLOT




#### POLAR CANDELA DISTRIBUTION



#### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30	851.3	26.4%
0-40	1,394.4	43.3%
0-60	2,480.6	77%
60-90	739.8	23%
70-100	326.1	10.1%
90-120	0.0	0%
0-90	3,220.4	100%
90-180	0.2	0%
0-180	3,220.6	100%

#### FLUX CHART



Height ■ Vertical Spread: 110.1°  
 ■ Horizontal Spread: 118.8°




# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE


### PHOTOMETRIC SPECIFICATIONS (CONTINUED)

KT-CBLED35PS-22C-8CSA-VDIM /CR

#### ISOCANDELA PLOT




#### POLAR CANDELA DISTRIBUTION




#### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30	1,123.7	26.4%
0-40	1,840.6	43.2%
0-60	3,275.0	76.9%
60-90	981.0	23%
70-100	434.1	10.2%
90-120	0.1	0%
0-90	4,256.0	100%
90-180	1.0	0%
0-180	4,257.0	100%

#### FLUX CHART






# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE


### PHOTOMETRIC SPECIFICATIONS (CONTINUED)

KT-CBLED30PS-24C-8CSA-VDIM /CR

#### ISOCANDELA PLOT




#### POLAR CANDELA DISTRIBUTION




#### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30	1,025.7	26.3%
0-40	1,682.1	43.1%
0-60	2,998.1	76.7%
60-90	909.1	23.3%
70-100	406.4	10.4%
90-120	0.0	0%
0-90	3,907.2	100%
90-180	0.0	0%
0-180	3,907.2	100%

#### FLUX CHART






# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE


### PHOTOMETRIC SPECIFICATIONS (CONTINUED)

KT-CBLED45PS-24C-8CSA-VDIM /CR

#### ISOCANDELA PLOT




#### POLAR CANDELA DISTRIBUTION



#### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30	1,523.0	26.2%
0-40	2,497.5	42.9%
0-60	4,452.5	76.5%
60-90	1,360.6	23.4%
70-100	612.9	10.5%
90-120	3.5	0.1%
0-90	5,813.1	99.9%
90-180	4.8	0.1%
0-180	5,817.9	100%

#### FLUX CHART







# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX


LED CENTER BASKET FIXTURE

## WIRING DIAGRAMS



## PHYSICAL SPECIFICATIONS





# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE

### ACCESSORIES

#### SENSORS

**Factory-Installable OR Field-Installable** (field-installable purchased separately)


✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/FC5	KTSL-FC5-12V-IM-PIR	Bluetooth mesh wireless low voltage individual fixture controller for LLLC SmartLoop system with integrated daylight and PIR motion sensors, 12V, 0-10V Dimming, Integral mount	843654164342	ODF-32



#### CORD SETS


**Factory-Installable OR Field-Installable** (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/515P6	KT-CS-515P-6-18/3	Cord set for high bay; 125V NEMA 5-15P; straight blade plug; 6' SJTOW cable; 18/3 wire	843654140124	UKH-26
	/MC13	KT-MC-NP-1-18/3	Metal clad cable for fixtures, No Plug, 1ft long, 18/3 wire (L,N,G)	843654139777	AYT-71
	/MC63	KT-MC-NP-6-18/3	Metal clad cable for fixtures. No Plug. 6ft long. 18/3 wire (L,N,G)	843654134505	EYP-82
	/MC65	KT-MC-NP-6-18/5	Metal clad cable for fixtures. No Plug. 6ft long. 18/5 wire (L,N,G, LV)	843654134512	CBU-56
	/MC66	KT-MC-NP-6-18/6	Metal clad cable for fixtures. No Plug. 6ft long. 18/6 wire (L,S,N,G, LV)	843654164229	KFF-99



\* FOR FACTORY INSTALLATION OF ACCESSORY, ADD SUFFIX TO FIXTURE PART NUMBER (SEE ORDERING EXAMPLES AND INSTRUCTIONS ON LAST PAGE OF SPEC SHEET).  
**NOTE:** FOR CORD SETS NOT LISTED HERE, PLEASE CONTACT YOUR KEYSTONE SALES REP.

(Accessories continued on next page)



# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE

### ACCESSORIES (CONTINUED)

#### EMERGENCY BACKUP

**Factory-Installable OR Field-Installable** (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/EM4	KT-EMRG-LED-4BC-400-EN2	4W, 400 lumen Smart Safe Emergency Backup, CEC T20 Compliant	843654175515	DQN-36
	/EM5†	KT-EMRG-LED-5C-500-EN /DF	5W, 500 Lumen Smart Safe Emergency Backup with Dual Flex, CEC T20 Compliant	843654132433	RAR-74
	/EM10†	KT-EMRG-LED-10BC-1000-EN3 /DF	10W, 1000 Lumen Smart Safe Emergency Backup with Dual Flex, CEC T20 Compliant	843654167619	KNI-42
	/EM12†	KT-EMRG-LED-12C-1200-EN /DF	12W, 1200 Lumen Smart Safe Emergency Backup with Dual Flex, CEC T20 Compliant	843654103112	OJQ-32



4W, 400 lumen Battery Backup  
KT-EMRG-LED-4BC-400-EN2



5W, 500 lumen Battery Backup  
KT-EMRG-LED-5C-500-EN /DF



10W, 1000 lumen Battery Backup  
KT-EMRG-LED-10BC-1000-EN3 /DF



12W, 1200 lumen Battery Backup  
KT-EMRG-LED-12C-500-EN /DF

\* FOR FACTORY INSTALLATION OF ACCESSORY, ADD SUFFIX TO FIXTURE PART NUMBER (SEE ORDERING EXAMPLES AND INSTRUCTIONS ON LAST PAGE OF SPEC SHEET).  
† FACTORY INSTALLATION OF EMERGENCY BACKUP UNITS WILL AUTOMATICALLY INCLUDE ANY RELEVANT MOUNTING BRACKET.

**Field-Installable / Field-Use ONLY** (purchased separately)

CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
KT-CBLEDC-EM-KIT	Emergency LED Backup Mounting Kit for Keystone Center Basket Troffers. (Style C) Includes Bracket and mounting hardware.	843654164779	YLG-39

#### MOUNTS AND BRACKETS

**Field-Installable / Field-Use ONLY** (purchased separately)


CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
KT-CBLEDC-SM-24-KIT	Surface Mount Kit for 2x4 LED Center Basket Troffers	843654127606	QWL-39
KT-CBLEDC-RMF-24-KIT	Recessed Mount Flange Kit for 2x4 Center Basket Fixtures	843654132976	UIO-18
KT-CBLEDC-SM-14-KIT	Surface Mount Kit for 1x4 LED Center Basket Troffers	843654127583	EUW-25
KT-CBLEDC-RMF-14-KIT	Recessed Mount Flange Kit for 1x4 Center Basket Fixtures	843654132952	GUY-89
KT-CBLEDC-SM-22-KIT	Surface Mount Kit for 2x2 LED Center Basket Troffers	843654127590	WVD-92
KT-CBLEDC-RMF-22-KIT	Recessed Mount Flange Kit for 2x2 Center Basket Fixtures	843654132969	IGR-64



Surface Mount Kit  
KT-CBLEDC-SM-24-KIT



Recessed Mount Flange Kit  
KT-CBLEDC-RMF-24-KIT



# KT-CBLEDXXPS-XXC-8CSA-VDIM /XX

## LED CENTER BASKET FIXTURE

### ORDERING INFORMATION

Catalog Number	Description	UPC	Easy Code	DLC PRODUCT ID
KT-CBLEDX35PS-14C-8CSA-VDIM /CR	1x4 LED Center Basket Troffer Power Select 35/30/24W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off	843654164700	QBB-35	S-0ZTXKX
KT-CBLEDX24PS-22C-8CSA-VDIM /CR	2x2 LED Center Basket Troffer Power Select 24/18/15W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off	843654164717	QPQ-68	S-6ZKB2T
KT-CBLEDX35PS-22C-8CSA-VDIM /CR	2x2 LED Center Basket Troffer Power Select 35/30/24W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off	843654164724	DGS-71	S-T0T3HF
KT-CBLEDX30PS-24C-8CSA-VDIM /CR	2x4 LED Center Basket Troffer Power Select 20/25/20W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off	843654164731	FIZ-47	S-7V65G4
KT-CBLEDX45PS-24C-8CSA-VDIM /CR	2x4 LED Center Basket Troffer Power Select 45/38/30W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off	843654164748	NBT-58	S-71R480
KT-CBLEDX35PS-14C-8CSA-VDIM /FC5	1x4 LED Center Basket Troffer Power Select 35/30/24W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off   Includes KTSL-FC5-12V-IM-PIR Preinstalled	843654166957	BIV-96	S-0ZTXKX
KT-CBLEDX24PS-22C-8CSA-VDIM /FC5	2x2 LED Center Basket Troffer Power Select 24/18/15W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off   Includes KTSL-FC5-12V-IM-PIR Preinstalled	843654166964	NVA-42	S-6ZKB2T
KT-CBLEDX35PS-22C-8CSA-VDIM /FC5	2x2 LED Center Basket Troffer Power Select 35/30/24W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off   Includes KTSL-FC5-12V-IM-PIR Preinstalled	843654166971	SSN-75	S-T0T3HF
KT-CBLEDX30PS-24C-8CSA-VDIM /FC5	2x4 LED Center Basket Troffer Power Select 20/25/20W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off   Includes KTSL-FC5-12V-IM-PIR Preinstalled	843654166988	WSG-70	S-7V65G4
KT-CBLEDX45PS-24C-8CSA-VDIM /FC5	2x4 LED Center Basket Troffer Power Select 45/38/30W & Color Select 3500/4000/5000K   120-277V Input  Frosted Curved Lens   0-10V Dimming   12V Aux + Dim to off   Includes KTSL-FC5-12V-IM-PIR Preinstalled	843654166995	GFL-90	S-71R480

