

LAMP READY LINEAR UTILITY STRIP LSS SERIES



LSS1XT8USE4802 Model



FEATURES:

- Designed for LED Single/Double Ended lamps – **lamps supplied separately**
- Maximum Photometric Efficiency with directional lamps
- Wire Tie tabs std. with fixture, Cable kit mounting accessory available
- Key Hole slots at rear for surface mounting
- Knockouts on each end for motion sensor mounting
- 5-Year Warranty

CONSTRUCTION:

- 24 Gauge Steel, white post painted baked on enamel.
- Damp rated housings
- Supplied with ONLY Non-Shunted sockets and Single ended wiring configurations. For questions contact MaxLite
- 600V rated UL Listed sockets

CONTROL:

- Optional Occupancy sensor available* (on/off)
- MSO option is only for the 2 lamp strip

HIGHLIGHTS
100% Digital PIR (Passive Infrared) Detection – on/off function
Can adjust sensitivity of PIR Detector (30% to 100%)
15-20 ft (4.57-6.10 m), 360° Radial Coverage Pattern, Covers up to 450 sq.ft
Self-Contained Relay, No Power Pack Needed
Interchangeable Hot & Load Wires
Adjustable Time Delay from 15 seconds to 30 minutes
No Field Calibration or Sensitivity Adjustments Required
10 years. Check maxlite.com/warranties for details

PRODUCT DESCRIPTION:

The MaxLite T8 LED "Lamp Ready" linear Utility Strip provides distributors, contractors, and buyers with a UL listed fixtures designed specifically for LED T8 lamps. These Linear Utility Strips are constructed of the same durable materials as commercial industrial grade fluorescent versions. These fixtures support competitive light output when used with MaxLite brand T8 LED Single/Double ended lamps. These fixtures are verified for use in task, general lighting, assembly, warehouse, and other general lighting applications

Single ended or Dual mode (Single/Double ended) T8 internal driver lamps (4') under 17W must be purchased separately from Maxlite for this product.

Refer to Maxlite website for the latest offering

<https://www.maxlite.com/products/ul-type-b-ballast-bypass-t8/>

<https://www.maxlite.com/products/ul-type-b-ballast-bypass-double-ended-power-t8/>

ORDERING INFORMATION			
ORDER NUMBER	MODEL	DESCRIPTION	DIMENSIONS (L" x W" x H")
75302	LSS1XT8USE4802*	UTILITY STRIP LAMP READY 1XT8 LED 120-277V SINGLE ENDED 48L X 2W	48.2" x 2.0" x 1.6"
75303	LSS2XT8USE4803*	UTILITY STRIP LAMP READY 2XT8 LED 120-277V SINGLE ENDED 48L X 3W	48.2" x 2.8" x 1.6"

NOTES:

1. This product is specifically engineered and listed for use with MaxLite Single/Double Ended conductor LED lamps. Maximum lamp wattages cannot exceed stated levels without voiding warranty. Cannot use with any other brand of lamps.
2. *For ordering Occupancy sensor, add "MSO" suffix to model number. MSO option is only for the 2 lamp strip.
3. Wire guard not compatible with occupancy sensor model.

ACCESSORIES		
ORDER CODE	MODEL NUMBER	DESCRIPTION
76653	LSS1XT8WG	Wire guard- Utility Strip 1x8 4ft Lamp Ready Fixture
76654	LSS2XT8WG	Wire guard- Utility Strip 2x8 4ft Lamp Ready Fixture
75301	MLCHKLSS15	Cable Kit- Utility Strip Series 15' M 10 THRD Slot Nut

IMPORTANT WARNING:

